



Kaindl FLOORS

Recommended tender specification

Dated: March 2020

- 1 Quality Floors. Made in Salzburg. 2**
- 2 Environment and health – four reasons for Kaindl products 2**
- 3 Laminate..... 3**
 - 3.1 Classic Touch 3
 - 3.1.1 7.0 Standard board 3
 - 3.1.2 8.0 Standard board 3
 - 3.1.3 8.0 Wide board 4
 - 3.1.4 8.0 Tile..... 4
 - 3.1.5 8.0 Premium board 5
 - 3.2 Natural Touch 5
 - 3.2.1 8.0 Standard board 5
 - 3.2.2 8.0 Wide board 6
 - 3.2.3 10.0 Long board 6
 - 3.2.4 10.0 Premium board 7
 - 3.2.5 12.0 Standard board 7
 - 3.3 Easy Touch 8
 - 3.3.1 8.0 Premium board 8
 - 3.4 AQUApro 8
 - 3.4.1 8.0 Select..... 8
 - 3.4.2 12.0 Supreme HB texture..... 9
 - 3.4.3 12.0 Supreme CB texture 9
- 4 Design..... 10**
 - 4.1 RVC..... 10
 - 4.1.1 4.0 Design board 10
 - 4.2 SPC 10
 - 4.2.1 4.0 Compact board..... 10
 - 4.2.2 5.0 Compact board..... 11
 - 4.2.3 5.0 Compact tile 11
 - 4.3 HDF..... 12
 - 4.3.1 8.0 Medium board 12
- 5 Wood..... 12**
 - 5.1 8.5 Premium board 12
 - 5.2 8.5 Wide board 13

1 Quality Floors. Made in Salzburg.

The name Kaindl stands for floorings that are high quality, robust and lifelike. In our collection, you will find floorings made regionally in Austria that model themselves on nature and new designs that have the potential to become trendsetters. With a large number of surfaces and all kinds of different board sizes, there is something suitable for every area of use.

Wood

Warm, vivid and ecologically valuable. The feel, smell and natural surface make Kaindl Veneer Parquet wooden floorings something very special. A piece of nature in your own four walls.

Laminate

Innovative and high quality. As a renowned flooring manufacturer, Kaindl benefits from it decades of experience. The result is a laminate flooring that has convincing technical refinements and decors that set trends throughout the industry.

AQUApro

A new generation of water resistance. With their authentic wood surface and water resistant joints, our AQUApro category floorings are a real highlight. They are also scratch, impact and stain resistant.

Design

Particularly hardwearing. SOLID design floorings not only look impressive. They also withstand plenty. The latest generation of vinyl flooring is resistant to moisture and dirt and is therefore suitable for all living areas.

2 Environment and health – four reasons for Kaindl products

Sustainable forestry

We preferably use wood assortments from PEFC-certified forests for the substrates of our floorings and boards.

Renewable energy

Optimisation of energy use has not only reduced consumption significantly, but has also led to extensive removal of fossil energy sources.

Low-emission production and products

By using completely new technologies, we were able to achieve a radical reduction in the exhaust air emissions of our production. The “GREENGUARD” label confirms that our products are sustainably healthy and low-emission. This ensures high room air quality.

Recycling instead of hazardous waste

Kaindl floorings and wood-based panels are 86% made of wood. They are not classified as hazardous waste and, even many years later, can therefore be disposed of easily, in terms of both energy and material aspects.

3 Laminate

3.1 Classic Touch

3.1.1 7.0 Standard board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, hotel rooms and small offices)

Description

Laminate flooring with use class 31/AC3 to EN 13329, formaldehyde emission E1

- Low-swelling HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Angle
- Thermal resistance 0.069 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

15 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 7 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.1.2 8.0 Standard board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.1.3 8.0 Wide board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Angle
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 244 x 8 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

3.1.4 8.0 Tile

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1285 x 327 x 8 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €



3.1.5 8.0 Premium board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

- Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1
- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.2 Natural Touch

3.2.1 8.0 Standard board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

- Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1
- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €



3.2.2 8.0 Wide board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Angle
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 244 x 8 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

3.2.3 10.0 Long board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 2000 x 192 x 10 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

3.2.4 10.0 Premium board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 10 mm

Decor and texture: _____

Alternative product: _____

Laying _____ €/ m²

Final cleaning _____ €

3.2.5 12.0 Standard board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 33/AC5 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 12 mm

Decor and texture: _____

Alternative product: _____

Laying _____ €/ m²

Final cleaning _____ €

3.3 Easy Touch

3.3.1 8.0 Premium board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate floorings with directly applied printing, use class 32/AC4 to EN 15468, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Coating made of multi-layer UV lacquer, digital printing and lacquer backing
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.4 AQUApro

3.4.1 8.0 Select

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Aquatec HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.4.2 12.0 Supreme HB texture

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Aquatec HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

35 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1287 x 192 x 12 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

3.4.3 12.0 Supreme CB texture

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Aquatec HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

35 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1290 x 193 x 12 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

4 Design

4.1 RVC

4.1.1 4.0 Design board

Areas of application

For laying as floating flooring, for internal use in dry conditions (open plan offices, department stores, multi-purpose hall-type buildings and main halls in railway stations)

Description

Rigid vinyl flooring, use class 34 to EN 16511

- Hard vinyl substrate with resistant UV varnish surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.099 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1280 x 192 x 4 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

4.2 SPC

4.2.1 4.0 Compact board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Mineral vinyl flooring, use class 32 to EN 16511

- Mineral vinyl substrate with resistant UV lacquer surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.437 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

25 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1210x 192 x 4 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

4.2.2 5.0 Compact board

Areas of application

For laying as floating flooring, for internal use in dry conditions (open plan offices, department stores, multi-purpose hall-type buildings and main halls in railway stations)

Description

Mineral vinyl flooring, use class 34 to EN 16511

- Mineral vinyl substrate with resistant UV lacquer surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.437 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1210 x 192 x 5 mm

Decor and texture: _____

Alternative product: _____

Laying _____ €/ m²

Final cleaning _____ €

4.2.3 5.0 Compact tile

Areas of application

For laying as floating flooring, for internal use in dry conditions (open plan offices, department stores, multi-purpose hall-type buildings and main halls in railway stations)

Description

Mineral vinyl flooring, use class 34 to EN 16511

- Mineral vinyl substrate with resistant UV lacquer surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.437 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 600 x 295 x 5 mm

Decor and texture: _____

Alternative product: _____

Laying _____ €/ m²

Final cleaning _____ €



4.3 HDF

4.3.1 8.0 Medium board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Hard vinyl flooring, use class 32 to EN 16511

- Low-swelling HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Resistant, resilient vinyl layer with decor film
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.1088 m² K/W to ISO 8302
- Reaction to fire Bfl-S1, to EN 13501-1

Decors

See <http://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 223 x 8 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

5 Wood

5.1 8.5 Premium board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, hotel rooms and small offices)

Description

Wooden flooring, use class 31 to EN 14354, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Wood veneer surface made of multi-layer, abrasion-resistant UV lacquer and wood veneer backing
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Dfl-S1, to EN 13501-1

Wood species

See <http://www.kaindl.com>

Guarantee

20 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 8.5 mm

Wood species and quality: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

5.2 8.5 Wide board

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, hotel rooms and small offices)

Description

Wooden flooring, use class 31 to EN 14354, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Wood veneer surface made of multi-layer, abrasion-resistant UV lacquer and wood veneer backing
- Glue-free, convenient laying system, Kaindl Loc: Angle/Angle
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Dfl-S1, to EN 13501-1

Wood species

See <http://www.kaindl.com>

Guarantee

20 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 244 x 8.5 mm

Wood species and quality: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €